



GAUGE COCKS

Gauge Cocks provide an economical way to shut off the flow of air to the pressure instrument, thereby allowing the instrument to be isolated from the pressure media or removed from service.

Generally used for pressure 400kgs.

Type of Gauge Cock

Two way gauge cock (2W)

three way gauge cock (3W)



DESCRIPTION

Accessory
Two way gauge cock (2W)
three way gauge cock (3W)

Material Used
SS304/316,
SS304L/SS316L,
CS

		Connection			
		Instrument			
Size	Type	Male/Female		Metric Threads	
6	1/4"	NT	NPT	M Male	18M – M18x1.5
10	3/8"	BP	BSP	F Female	20M – M20x1.5
15	1/2"	BT	BSPT		24M – M20x1.5
20	3/4"	PF	PF		27M – M27x1.5
25	1"	GS	Gas		33M – M33x1.5
		NS	NPS		

		Connection			
		Process			
Size	Type	Male/Female		Metric Threads	
6	1/4"	NT	NPT	M Male	18M – M18x1.5
10	3/8"	BP	BSP	F Female	20M – M20x1.5
15	1/2"	BT	BSPT		24M – M20x1.5
20	3/4"	PF	PF		27M – M27x1.5
25	1"	GS	Gas		33M – M33x1.5
		NS	NPS		